

## Data sheet

### SM 031 - Analog input (031-1PA00)

#### Technical data

<b>Order no.</b>	<b>031-1PA00</b>
Type	SM 031 - Analog input
Module ID	0882 2880
<b>General information</b>	
Note	-
Features	AI1x 3Ph 230/400 V 1 A Remanent storage of the energy values   diagnostic function Resolution measurement 24 Bit 3-phase and N-conductor Electrical efficiency   elektrical work Harmonic harmonics Phase delay cos Frequency
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	60 mA
Power loss	0.9 W
Rated load voltage	-
<b>Status information, alarms, diagnostics</b>	
Status display	yes
Interrupts	yes, parameterizable
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	yes, parameterizable
Diagnostics information read-out	possible
Module state	green LED
Module error display	red LED
Channel error display	-
<b>Isolation</b>	
Between channels	-
Insulation tested with	AC 2200 V
<b>Energy measurement</b>	
Number of channels for measuring	1* 1..3 phases U/I
Voltage measuring range	0..300 V each phase
Coupling voltage measurement	directly
Current range	0..1 A each phase
Coupling current measurement	Transformer
Frequency range	46...64 Hz
Measurement accuracy	1 %
Available measurement	Active energy Voltage RMS Current RMS Active power Reactive power Apparent power Cos phi Harmonic voltage RMS Harmonic current RMS Temperature Frequency

Adjustable limits

Voltage RMS min/max  
 Current RMS min/max  
 Cos phi min  
 Temperature max.  
 Frequency min/max

## Datasizes

Input bytes	16
Output bytes	16
Parameter bytes	28
Diagnostic bytes	20

## Housing

Material	PPE / PPE GF10
Mounting	Profile rail 35 mm

## Mechanical data

Dimensions (WxHxD)	12.9 mm x 109 mm x 76.5 mm
Net weight	57 g
Weight including accessories	57 g
Gross weight	71 g

## Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

## Certifications

UL certification	-
KC certification	-
UKCA certification	-
ChinaRoHS certification	-