

## Data sheet

### SM 021 - Digital input (021-1BD70)

#### Technical data

<b>Order no.</b>	<b>021-1BD70</b>
Type	SM 021 - Digital input
Module ID	0F03 47C2
<b>General information</b>	
Note	-
Features	4x DI DC 24 V Input filter time delay parameterizable 2 $\mu$ s...3 ms ETS function with $\mu$ sec time stamp
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	100 mA
Power loss	0.95 W
<b>Technical data digital inputs</b>	
Number of inputs	4
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated voltage power section supply	DC 24 V
Permitted range	DC 20.4...28.8 V
Current consumption from power section supply (without load)	15 mA
Input rated voltage	DC 24 V
Permitted range	DC 20.4...28.8 V
Input voltage for signal "0"	DC 0...5 V
Input voltage for signal "1"	DC 15...28.8 V
Input voltage hysteresis	-
Signal logic input	Sinking input
Frequency range	-
Input resistance	-
Input capacitance	-
Input current for signal "1"	3 mA
Connection of Two-Wire-BEROs possible	yes
Max. permissible BERO quiescent current	0.5 mA
Input delay of "0" to "1"	parameterizable 2 $\mu$ s - 3ms
Input delay of "1" to "0"	parameterizable 2 $\mu$ s - 3ms
Number of simultaneously utilizable inputs horizontal configuration	4
Number of simultaneously utilizable inputs vertical configuration	4
Input characteristic curve	IEC 61131-2, type 1
Initial data size	60 Byte
<b>Status information, alarms, diagnostics</b>	
Status display	green LED per channel
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no

Diagnostics information read-out	possible
Module state	green LED
Module error display	red LED
Channel error display	none

## Isolation

Between channels	-
Between channels of groups to	-
Between channels and backplane bus	yes
Insulation tested with	DC 500 V

## Datasizes

Input bytes	20 / 60
Output bytes	0
Parameter bytes	12
Diagnostic bytes	20

## Housing

Material	PPE / PPE GF10
Mounting	Profile rail 35 mm

## Mechanical data

Dimensions (WxHxD)	12.9 mm x 109 mm x 76.5 mm
Net weight	58 g
Weight including accessories	58 g
Gross weight	73 g

## Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

## Certifications

UL certification	yes
KC certification	yes
UKCA certification	yes
ChinaRoHS certification	yes