

## Data sheet CPU 313SC DPM (313-6CF23)

### Technical data

|   |   |
|---|---|
| <b>Order no.</b>  | <b>313-6CF23</b>  |
| Type  | CPU 313SC DPM   |
| <b>General information</b>                              |   |
| Note  | -   |
| Features  | Powered by SPEED7<br>Work memory [KB]: 256...1.024<br>Onboard: 16x DI / 16x DO / 3x Counter / 3x PWM<br>Interface [RJ45]: Ethernet PG/OP communication<br>Interface [2x RS485]: MPI, PROFIBUS master/slave, PTP:<br>ASCII, STX/ETX, 3964 (R), USS master, Modbus master/slave<br>Including front connector<br>SD/MMC card slot with locking, up to 32 modules stackable,<br>programmable with WinPLC7, SIMATIC Manager and TIA Portal |
| SPEED-Bus   | -   |
| <b>Technical data power supply</b>                      |   |
| Power supply (rated value)                              | DC 24 V   |
| Power supply (permitted range)                          | DC 20.4...28.8 V  |
| Reverse polarity protection                             | yes   |
| Current consumption (no-load operation)                 | 200 mA  |
| Current consumption (rated value)                       | 900 mA  |
| Inrush current  | 11 A  |
| $I^2t$  | 0.7 A <sup>2</sup> s  |
| Max. current drain at backplane bus                     | 3 A   |
| Max. current drain load supply                          | -   |
| Power loss  | 14 W  |
| <b>Technical data digital inputs</b>                    |   |
| Number of inputs  | 16  |
| Cable length, shielded                                  | 1000 m  |
| Cable length, unshielded                                | 600 m   |
| Rated load voltage                                      | DC 24 V   |
| Reverse polarity protection of rated load voltage       | yes   |
| Current consumption from load voltage L+ (without load) | 70 mA   |
| Rated value   | DC 24 V   |
| Input voltage for signal "0"                            | DC 0...5 V  |
| Input voltage for signal "1"                            | DC 15...28.8 V  |
| Input voltage hysteresis                                | -   |
| Signal logic input                                      | Sinking input   |
| Frequency range   | -   |
| Input resistance  | -   |
| Input current for signal "1"                            | 6 mA  |
| Connection of Two-Wire-BEROs possible                   | yes   |
| Max. permissible BERO quiescent current                 | 1.5 mA  |
| Input delay of "0" to "1"                               | 0.1 / 0.35 ms   |
| Input delay of "1" to "0"                               | 0.1 / 0.35 ms   |

|   |                     |
|---|---------------------|
| Number of simultaneously utilizable inputs horizontal configuration | 16                  |
| Number of simultaneously utilizable inputs vertical configuration   | 16                  |
| Input characteristic curve  | IEC 61131-2, type 1 |
| Initial data size   | 2 Byte              |

## Technical data digital outputs

|   |                 |
|---|-----------------|
| Number of outputs   | 16              |
| Cable length, shielded  | 1000 m          |
| Cable length, unshielded                                      | 600 m           |
| Rated load voltage  | DC 24 V         |
| Reverse polarity protection of rated load voltage             | -               |
| Current consumption from load voltage L+ (without load)       | 100 mA          |
| Total current per group, horizontal configuration, 40°C       | 3 A             |
| Total current per group, horizontal configuration, 60°C       | 2 A             |
| Total current per group, vertical configuration               | 2 A             |
| Output voltage signal "1" at min. current                     | L+ (-0.8 V)     |
| Output voltage signal "1" at max. current                     | L+ (-0.8 V)     |
| Output current at signal "1", rated value                     | 0.5 A           |
| Signal logic output   | Sourcing output |
| Output current, permitted range to 40°C                       | 5 mA to 0.6 A   |
| Output current, permitted range to 60°C                       | 5 mA to 0.6 A   |
| Output current at signal "0" max. (residual current)          | 0.5 mA          |
| Output delay of "0" to "1"                                    | 100 µs          |
| Output delay of "1" to "0"                                    | 100 µs          |
| Minimum load current  | -               |
| Lamp load   | 5 W             |
| Parallel switching of outputs for redundant control of a load | possible        |
| Parallel switching of outputs for increased power             | not possible    |
| Actuation of digital input                                    | yes             |
| Switching frequency with resistive load                       | max. 2.5 kHz    |
| Switching frequency with inductive load                       | max. 0.5 Hz     |
| Switching frequency on lamp load                              | max. 2.5 kHz    |
| Internal limitation of inductive shut-off voltage             | L+ (-52 V)      |
| Short-circuit protection of output                            | yes, electronic |
| Trigger level   | 1 A             |
| Number of operating cycle of relay outputs                    | -               |
| Switching capacity of contacts                                | -               |
| Output data size  | 2 Byte          |

## Technical data analog inputs

|   |   |
|---|---|
| Number of inputs  | - |
| Cable length, shielded                                  | - |
| Rated load voltage                                      | - |
| Reverse polarity protection of rated load voltage       | - |
| Current consumption from load voltage L+ (without load) | - |
| Voltage inputs  | - |
| Min. input resistance (voltage range)                   | - |
| Input voltage ranges                                    | - |
| Operational limit of voltage ranges                     | - |

|   |   |
|---|---|
| Operational limit of voltage ranges with SFU                | - |
| Basic error limit voltage ranges                            | - |
| Basic error limit voltage ranges with SFU                   | - |
| Destruction limit voltage                                   | - |
| Current inputs  | - |
| Max. input resistance (current range)                       | - |
| Input current ranges  | - |
| Operational limit of current ranges                         | - |
| Operational limit of current ranges with SFU                | - |
| Basic error limit current ranges                            | - |
| Radical error limit current ranges with SFU                 | - |
| Destruction limit current inputs (electrical current)       | - |
| Destruction limit current inputs (voltage)                  | - |
| Resistance inputs   | - |
| Resistance ranges   | - |
| Operational limit of resistor ranges                        | - |
| Operational limit of resistor ranges with SFU               | - |
| Basic error limit   | - |
| Basic error limit with SFU                                  | - |
| Destruction limit resistance inputs                         | - |
| Resistance thermometer inputs                               | - |
| Resistance thermometer ranges                               | - |
| Operational limit of resistance thermometer ranges          | - |
| Operational limit of resistance thermometer ranges with SFU | - |
| Basic error limit thermoresistor ranges                     | - |
| Basic error limit thermoresistor ranges with SFU            | - |
| Destruction limit resistance thermometer inputs             | - |
| Thermocouple inputs   | - |
| Thermocouple ranges   | - |
| Operational limit of thermocouple ranges                    | - |
| Operational limit of thermocouple ranges with SFU           | - |
| Basic error limit thermocouple ranges                       | - |
| Basic error limit thermocouple ranges with SFU              | - |
| Destruction limit thermocouple inputs                       | - |
| Programmable temperature compensation                       | - |
| External temperature compensation                           | - |
| Internal temperature compensation                           | - |
| Technical unit of temperature measurement                   | - |
| Resolution in bit   | - |
| Measurement principle                                       | - |
| Basic conversion time                                       | - |
| Noise suppression for frequency                             | - |
| Initial data size   | - |
| <b>Technical data analog outputs</b>                        |   |
| Number of outputs   | - |
| Cable length, shielded                                      | - |
| Rated load voltage  | - |
| Reverse polarity protection of rated load voltage           | - |

|   |   |
|---|---|
| Current consumption from load voltage L+ (without load) | - |
| Voltage output short-circuit protection                 | - |
| Voltage outputs   | - |
| Min. load resistance (voltage range)                    | - |
| Max. capacitive load (current range)                    | - |
| Max. inductive load (current range)                     | - |
| Output voltage ranges                                   | - |
| Operational limit of voltage ranges                     | - |
| Basic error limit voltage ranges with SFU               | - |
| Destruction limit against external applied voltage      | - |
| Current outputs   | - |
| Max. in load resistance (current range)                 | - |
| Max. inductive load (current range)                     | - |
| Typ. open circuit voltage current output                | - |
| Output current ranges                                   | - |
| Operational limit of current ranges                     | - |
| Radical error limit current ranges with SFU             | - |
| Destruction limit against external applied voltage      | - |
| Settling time for ohmic load                            | - |
| Settling time for capacitive load                       | - |
| Settling time for inductive load                        | - |
| Resolution in bit                                       | - |
| Conversion time   | - |
| Substitute value can be applied                         | - |
| Output data size  | - |

## Technical data counters

|                          |        |
|--------------------------|--------|
| Number of counters       | 3      |
| Counter width            | 32 Bit |
| Maximum input frequency  | 30 kHz |
| Maximum count frequency  | 30 kHz |
| Mode incremental encoder | yes    |
| Mode pulse / direction   | yes    |
| Mode pulse               | yes    |
| Mode frequency counter   | yes    |
| Mode period measurement  | yes    |
| Gate input available     | yes    |
| Latch input available    | yes    |
| Reset input available    | -      |
| Counter output available | yes    |

## Load and working memory

|  |                            |
|--|----------------------------|
| Load memory, integrated                  | 1024 KB                    |
| Load memory, maximum                     | 1024 KB                    |
| Work memory, integrated                  | 256 KB                     |
| Work memory, maximal                     | 1024 KB                    |
| Memory divided in 50% program / 50% data | yes                        |
| Memory card slot                         | SD/MMC-Card with max. 2 GB |

## Hardware configuration

|             |   |
|-------------|---|
| Racks, max. | 4 |
|-------------|---|

|                                    |   |
|------------------------------------|---|
| Modules per rack, max.             | 8 |
| Number of integrated DP master     | 1 |
| Number of DP master via CP         | 4 |
| Operable function modules          | 8 |
| Operable communication modules PtP | 8 |
| Operable communication modules LAN | 8 |

## Status information, alarms, diagnostics

|                                  |                   |
|----------------------------------|-------------------|
| Status display                   | yes               |
| Interrupts                       | yes               |
| Process alarm                    | yes               |
| Diagnostic interrupt             | yes               |
| Diagnostic functions             | no                |
| Diagnostics information read-out | possible          |
| Supply voltage display           | green LED         |
| Group error display              | red SF LED        |
| Channel error display            | red LED per group |

## Isolation

|   |                  |
|---|------------------|
| Between channels  | yes              |
| Between channels of groups to                               | 16               |
| Between channels and backplane bus                          | yes              |
| Between channels and power supply                           | -                |
| Max. potential difference between circuits                  | DC 75 V/ AC 50 V |
| Max. potential difference between inputs (Ucm)              | -                |
| Max. potential difference between Mana and Mintern (Uiso)   | -                |
| Max. potential difference between inputs and Mana (Ucm)     | -                |
| Max. potential difference between inputs and Mintern (Uiso) | -                |
| Max. potential difference between Mintern and outputs       | -                |
| Insulation tested with                                      | DC 500 V         |

## Command processing times

|                                 |              |
|---------------------------------|--------------|
| Bit instructions, min.          | 0.02 $\mu$ s |
| Word instruction, min.          | 0.02 $\mu$ s |
| Double integer arithmetic, min. | 0.02 $\mu$ s |
| Floating-point arithmetic, min. | 0.12 $\mu$ s |

## Timers/Counters and their retentive characteristics

|                                 |                        |
|---------------------------------|------------------------|
| Number of S7 counters           | 512                    |
| S7 counter remanence            | adjustable 0 up to 256 |
| S7 counter remanence adjustable | C0 .. C7               |
| Number of S7 times              | 512                    |
| S7 times remanence              | adjustable 0 up to 256 |
| S7 times remanence adjustable   | not retentive          |

## Data range and retentive characteristic

|  |                        |
|--|------------------------|
| Number of flags                                  | 8192 Byte              |
| Bit memories retentive characteristic adjustable | adjustable 0 up to 256 |
| Bit memories retentive characteristic preset     | MB0 .. MB15            |
| Number of data blocks                            | 4095                   |
| Max. data blocks size                            | 64 KB                  |
| Max. local data size per execution level         | 510 Byte               |

## Blocks

|   |      |
|---|------|
| Number of OBs                                       | 15   |
| Number of FBs                                       | 2048 |
| Number of FCs                                       | 2048 |
| Maximum nesting depth per priority class            | 8    |
| Maximum nesting depth additional within an error OB | 4    |

## Time

|                                    |              |
|------------------------------------|--------------|
| Real-time clock buffered           | yes          |
| Clock buffered period (min.)       | 6 w          |
| Accuracy (max. deviation per day)  | 10 s         |
| Number of operating hours counter  | 8            |
| Clock synchronization              | yes          |
| Synchronization via MPI            | Master/Slave |
| Synchronization via Ethernet (NTP) | no           |

## Address areas (I/O)

|                              |           |
|------------------------------|-----------|
| Input I/O address area       | 1024 Byte |
| Output I/O address area      | 1024 Byte |
| Input process image maximal  | 128 Byte  |
| Output process image maximal | 128 Byte  |
| Digital inputs               | 8064      |
| Digital outputs              | 8064      |
| Digital inputs central       | 1008      |
| Digital outputs central      | 1008      |
| Integrated digital inputs    | 16        |
| Integrated digital outputs   | 16        |
| Analog inputs                | 503       |
| Analog outputs               | 503       |
| Analog inputs, central       | 248       |
| Analog outputs, central      | 248       |
| Integrated analog inputs     | 0         |
| Integrated analog outputs    | 0         |

## Communication functions

|   |          |
|---|----------|
| PG/OP channel                             | yes      |
| Global data communication                 | yes      |
| Number of GD circuits, max.               | 4        |
| Size of GD packets, max.                  | 22 Byte  |
| S7 basic communication                    | yes      |
| S7 basic communication, user data per job | 76 Byte  |
| S7 communication                          | yes      |
| S7 communication as server                | yes      |
| S7 communication as client                | -        |
| S7 communication, user data per job       | 160 Byte |
| Number of connections, max.               | 32       |

## PWM data

|                     |                                   |
|---------------------|-----------------------------------|
| PWM channels        | 3                                 |
| PWM time basis      | 0.1 ms / 1 ms                     |
| Period length       | 4...65535 / 1...65535 * time base |
| Minimum pulse width | 0...0.5 * Period duration         |

Type of output Highside with 1.1kOhm pulldown

## Functionality Sub-D interfaces

|                          |                          |
|--------------------------|--------------------------|
| Type                     | X2                       |
| Type of interface        | RS485                    |
| Connector                | Sub-D, 9-pin, female     |
| Electrically isolated    | -                        |
| MPI                      | yes                      |
| MP2I (MPI/RS232)         | -                        |
| DP master                | -                        |
| DP slave                 | -                        |
| Point-to-point interface | -                        |
| 5V DC Power supply       | max. 90mA, non-isolated  |
| 24V DC Power supply      | max. 100mA, non-isolated |

|                          |                          |
|--------------------------|--------------------------|
| Type                     | X3                       |
| Type of interface        | RS485                    |
| Connector                | Sub-D, 9-pin, female     |
| Electrically isolated    | yes                      |
| MPI                      | -                        |
| MP2I (MPI/RS232)         | -                        |
| DP master                | yes                      |
| DP slave                 | yes                      |
| Point-to-point interface | yes                      |
| 5V DC Power supply       | max. 90mA, isolated      |
| 24V DC Power supply      | max. 100mA, non-isolated |

## Functionality MPI

|                             |              |
|-----------------------------|--------------|
| Number of connections, max. | 32           |
| PG/OP channel               | yes          |
| Routing                     | yes          |
| Global data communication   | yes          |
| S7 basic communication      | yes          |
| S7 communication            | yes          |
| S7 communication as server  | yes          |
| S7 communication as client  | -            |
| Transmission speed, min.    | 19.2 kbit/s  |
| Transmission speed, max.    | 187.5 kbit/s |

## Functionality PROFIBUS master

|   |            |
|---|------------|
| Number of connections, max.                         | 32         |
| PG/OP channel                                       | yes        |
| Routing   | yes        |
| S7 basic communication                              | yes        |
| S7 communication                                    | yes        |
| S7 communication as server                          | yes        |
| S7 communication as client                          | -          |
| Activation/deactivation of DP slaves                | yes        |
| Direct data exchange (slave-to-slave communication) | -          |
| DPV1  | yes        |
| Transmission speed, min.                            | 9.6 kbit/s |

|                                   |           |
|-----------------------------------|-----------|
| Transmission speed, max.          | 12 Mbit/s |
| Number of DP slaves, max.         | 32        |
| Address range inputs, max.        | 1 KB      |
| Address range outputs, max.       | 1 KB      |
| User data inputs per slave, max.  | 244 Byte  |
| User data outputs per slave, max. | 244 Byte  |

## Functionality PROFIBUS slave

|   |            |
|---|------------|
| Number of connections, max.                         | 32         |
| PG/OP channel                                       | yes        |
| Routing   | yes        |
| S7 communication                                    | yes        |
| S7 communication as server                          | yes        |
| S7 communication as client                          | -          |
| Direct data exchange (slave-to-slave communication) | -          |
| DPV1  | yes        |
| Transmission speed, min.                            | 9.6 kbit/s |
| Transmission speed, max.                            | 12 Mbit/s  |
| Automatic detection of transmission speed           | -          |
| Transfer memory inputs, max.                        | 244 Byte   |
| Transfer memory outputs, max.                       | 244 Byte   |
| Address areas, max.                                 | 32         |
| User data per address area, max.                    | 32 Byte    |

## Functionality RJ45 interfaces

|                             |                      |
|-----------------------------|----------------------|
| Type                        | X5                   |
| Type of interface           | Ethernet 10/100 MBit |
| Connector                   | RJ45                 |
| Electrically isolated       | yes                  |
| PG/OP channel               | yes                  |
| Number of connections, max. | 4                    |
| Productive connections      | -                    |

## Point-to-point communication

|                          |                      |
|--------------------------|----------------------|
| PtP communication        | yes                  |
| Interface isolated       | yes                  |
| RS232 interface          | -                    |
| RS422 interface          | -                    |
| RS485 interface          | yes                  |
| Connector                | Sub-D, 9-pin, female |
| Transmission speed, min. | 150 bit/s            |
| Transmission speed, max. | 115.5 kbit/s         |
| Cable length, max.       | 500 m                |

## Point-to-point protocol

|                        |     |
|------------------------|-----|
| ASCII protocol         | yes |
| STX/ETX protocol       | yes |
| 3964(R) protocol       | yes |
| RK512 protocol         | -   |
| USS master protocol    | yes |
| Modbus master protocol | yes |
| Modbus slave protocol  | -   |



Special protocols -

## Housing

Material PPE

Mounting Rail System 300

## Mechanical data

Dimensions (WxHxD) 80 mm x 125 mm x 120 mm

Net weight 420 g

Weight including accessories -

Gross weight -

## Environmental conditions

Operating temperature 0 °C to 60 °C

Storage temperature -25 °C to 70 °C

## Certifications

UL certification yes

KC certification yes