

## Data sheet

### smartPanel TP307-SM (H71-71A41-0)

#### Technical data

<b>Order no.</b>	<b>H71-71A41-0</b>
Type	smartPanel TP307-SM
<b>General information</b>	
Note	-
Features	Display: 7" Processor: Cortex-A8   1GHz Work memory [MB]: 512 User memory [GB]: 4 Interface onboard: 1x RS232/422/485   1x USB-A   1x RJ45 (Ethernet) Software: WEC 7   Movicon 11 CE Standard
<b>Display</b>	
Display size (diagonal)	7 "
Display size (width)	155 mm
Display size (height)	88 mm
Resolution	480 x 800 / 800 x 480
Aspect ratio	16:9
Type of display	TFT color (64K colors)
MTBF Backlights (25°C)	20000 h
<b>System properties</b>	
Processor	Cortex-A8 1000 MHz
Operating system	Windows Embedded Compact 7
User software	Movicon 11 CE Standard
Work memory	512 MB
User memory	4 GB
Available memory (user data)	2 GB
SD/MMC Slot	-
CF Card Slot Typ II	-
CFast Slot	-
<b>Time</b>	
Real-time clock buffered	yes
Clock buffered period (min.)	2 w
Type of buffering	Goldcap
Load time for 50% buffering period	5 h
Load time for 100% buffering period	10 h
Accuracy (max. deviation per day)	8 s
<b>Operating controls</b>	
Touchscreen	resistive
Touch function	Single Touch
Keyboard	external via USB
Mouse	external via USB
<b>Interfaces</b>	
MPI, PROFIBUS-DP	-
MPI, PROFIBUS-DP connector	-
Serial, COM1	RS232 / RS422 / RS485

COM1 connector	Sub-D, 9-pin, male
Serial, COM2	-
COM2 connector	-
Number of USB-A interfaces	1
USB-A connector	USB-A (host)
Number of USB-B interfaces	-
USB-B connector	-
Number of ethernet interfaces	1
Ethernet	Ethernet 10/100 MBit
Ethernet connector	RJ45
Integrated ethernet switch	-
Video connectors	-
Audio connections	-

## Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	18 - 32 VDC
Reverse polarity protection	yes
Current consumption (no-load operation)	0.1 A
Current consumption (rated value)	0.3 A
Inrush current	38 A
$I^2t$	0.33 A <sup>2</sup> s
Power loss	7 W

## Status information, alarms, diagnostics

Status display	none
Supply voltage display	none

## Mechanical data

### Housing / Protection class

Material	PC + ABS
Mounting	mounting clips
Protection class IP front side	IP 66
Protection class IP back side	IP 20
Protection class NEMA front side	Type 2, 4X
Protection class NEMA back side	-

## Dimensions

Front panel	187 mm x 147 mm x 5 mm
Rear panel	172 mm x 133 mm x 29 mm

## Installation cut-out

Width	176 mm
Height	136 mm
Minimum	1.5 mm
Maximum front panel thickness	6 mm
Net weight	500 g
Weight including accessories	631 g
Gross weight	900 g

## Environmental conditions

Operating temperature	0 °C to 50 °C
Storage temperature	-20 °C to 70 °C

## Certifications

UL certification	yes
KC certification	-
UKCA certification	-
ChinaRoHS certification	-
DNV certification	-
EU MR certification	-