

Data sheet

Panel PC PPC010 IE (67K-RTP0-KB)

Technical data

Order no.	67K-RTP0-KB
------------------	--------------------

Type	Panel PC PPC010 IE
------	--------------------

General information

Note	-
------	---

Features	Display: 10.1" Processor: Intel Celeron J1900 quad core @2 GHz Work memory: 8 GB Operating system and user memory: 64 GB Memory card plug-in place: CFast Interfaces: 2x Ethernet (10/100/1000), 2x USB 2.0, 1x USB 3.0, 2x serial (RS232,RS422/RS485), 1x serial VGA, 1x remote power switch, Audio out Software: Windows 10 IoT Enterprise Visualization system: Movicon 11.6 Runtime - 128 I/Os
----------	---

Display

Display size (diagonal)	10.1 "
-------------------------	--------

Display size (width)	217 mm
----------------------	--------

Display size (height)	136 mm
-----------------------	--------

Resolution	800 x 1280 / 1280 x 800
------------	-------------------------

Aspect ratio	16:10
--------------	-------

Type of display	TFT color (262K colors)
-----------------	-------------------------

MTBF Backlights (25°C)	50000 h
------------------------	---------

System properties

Processor	Intel Celeron Quad core 2 GHz
-----------	-------------------------------

Operating system	Windows 10 IoT Enterprise 64Bit
------------------	---------------------------------

User software	Movicon 11 Win Standard
---------------	-------------------------

Work memory	8 GB
-------------	------

User memory	64 GB
-------------	-------

Available memory (user data)	42 GB
------------------------------	-------

SD/MMC Slot	-
-------------	---

CF Card Slot Typ II	-
---------------------	---

CFast Slot	yes
------------	-----

Time

Real-time clock buffered	yes
--------------------------	-----

Clock buffered period (min.)	4 y
------------------------------	-----

Type of buffering	lithium battery
-------------------	-----------------

Load time for 50% buffering period	-
------------------------------------	---

Load time for 100% buffering period	-
-------------------------------------	---

Accuracy (max. deviation per day)	10 s
-----------------------------------	------

Operating controls

Touchscreen	PCAP
-------------	------

Touch function	Multi Touch
----------------	-------------

Keyboard	external via USB
----------	------------------

Mouse	external via USB
-------	------------------

Interfaces

MPI, PROFIBUS-DP	-
------------------	---

MPI, PROFIBUS-DP connector	-
Serial, COM1	RS232 / RS422 / RS485
COM1 connector	Sub-D, 9-pin, male
Serial, COM2	RS232 / RS422 / RS485
COM2 connector	Sub-D, 9-pin, male
Number of USB-A interfaces	3
USB-A connector	USB-A (host)
Number of USB-B interfaces	-
USB-B connector	-
Number of ethernet interfaces	2
Ethernet	Ethernet 10/100/1000 MBit
Ethernet connector	2 x RJ45
Integrated ethernet switch	-
Video connectors	VGA SubD HD15
Audio connections	Line out, stereo jack 3.5 mm

Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	0.12 A
Current consumption (rated value)	0.52 A
Inrush current	-
I^2t	0.3 A ² s
Power loss	13 W

Status information, alarms, diagnostics

Status display	none
Supply voltage display	none

Mechanical data

Housing / Protection class

Material	coated aluminium steel plate
Mounting	via integrated pivoted lever
Protection class IP front side	IP 66
Protection class IP back side	IP 20
Protection class NEMA front side	-
Protection class NEMA back side	-

Dimensions

Front panel	308 mm x 223 mm x 6.7 mm
Rear panel	292 mm x 207 mm x 54.2 mm

Installation cut-out

Width	297 mm
Height	212 mm
Minimum	3 mm
Maximum front panel thickness	12 mm
Net weight	3.72 kg
Weight including accessories	4.52 kg
Gross weight	4.52 kg

Environmental conditions

Operating temperature	-10 °C to 60 °C
-----------------------	-----------------

Storage temperature -20 °C to 75 °C

Certifications	
UL certification	yes
KC certification	-
UKCA certification	-
ChinaRoHS certification	-
DNV certification	-
EU MR certification	-